

OVERCOAT™ Z

Product Information Sheet

Description

OVERCOAT Z is an efficient, cost-effective non-pigmented anti-tack Dry Dispersion™ based on zinc stearate. Use level solids varies between 2% and 10% depending on the nature of the stock.


OVERCOAT Z does not contain alcohol, glycerine, silicone, talc, petroleum distillate (aka hydrotreated distillate), SARA reportable compounds, or VOCs of any kind. OVERCOAT Z does not contain quartz or respirable quartz fractions.

Performance Advantages

- OVERCOAT Z is hydrated in-plant by our CONSTITUTER™ or CONSTITUTER MASTER MIX STATION™.
- Coats all stocks effectively – including low durometer and oil-filled stocks.
- The coating on the stock is uniform, non-dusting, non-greasy and quick-drying.
- Virtually foam free and does not sludge out on standing in the dip tank.
- Save half or more on inbound shipping because we do not ship water.
- Reduced in-plant storage space and no need to protect from freezing.
- Thickening of product in storage is eliminated.
- Disposal or return of pails, drums and tote bins is eliminated.
- No harmful petroleum distillates, alcohol, glycerine, silicone, talc, EDTA, or VOCs.

Product Specifications

Appearance	Off-white dry blend
Solids	97 – 100%
pH	8.5 – 10.5 (2% dispersion)



Instructions For Use

Add OVERCOAT Z to the CONSTITUTER™ or CONSTITUTER MASTER MIX STATION™ for automated hydration. The CONSTITUTER or DIP TANK MANAGER™ robots connected to the MASTER MIX STATION will automatically manage the dip tank's percent solids level.

Packaging

OVERCOAT Z is packaged in 25 pound bags and bulk bags.

Handling and Storage

There are no special handling or storage requirements. Please refer to the SDS for safety information.